



MCH 16ET

The MCH 16ET is a compact three phase, 3 stage semi sound proofed compressor offering reliability and a choice of pressures. A very low turning speed coupled with excellent filtration ensures safe and reliable operation. The breathing air filtration ensures air quality to the highest standards meeting DIN 3188. This unit has 2 hoses on the front for filling direct into high-pressure cylinders or can be piped to a high-pressure storage bank with filling panel.

Features

- Powder coated steel frame
- Auto drain and auto stop as standard
- Oil level indication with sight glass
- Emergency stop
- Large capacity oil sump
- Oil and water separators
- Breathing air purification in accordance with DIN 3188



Specialists in Safety: BA Compressors

Total Protection (UK) Limited

Tel: 0844 576 7423

info@totalprotectionuk.com

www.totalprotectionuk.com



Technical Data

Model compressor	MCH 16 ET	
Working pressure	200 Bar	300 Bar
Charging rate	265 l/min 16m ³ /h 9.3 cfm	265 l/min 16m ³ /h 9.3 cfm

Frame	Powder Coated Steel
Number of stages	3
Lubricating oil capacity	1.6 litres
RPM Pumping Unit	1,550
Oil type	Coltri CE 750 Lubricant
Oil Mist Separator	2
Filtration	Active carbon cartridge & molecular sieve
Safety Valve	2 stage and final stage
Interstage coolers and after coolers	Stainless steel
Breathing air	DIN 3188
Filling time (10 litres 0-200 bar)	8 minutes

Drive	Three Phase Electric Motor
Operating Voltage	400v
Power	5.5 kW
Noise Level	81 dB
Weight	151 Kg
Dimensions (H x L x W) cm	84 x 89 x 60

Product Warranty

12 Months Full RTB Parts & Labour Guarantee
Full optional on-site service available

Total Protection (UK) Limited

Tel: 0844 567 7423

info@totalprotectionuk.com

www.totalprotectionuk.com

Specialists in Safety: BA Compressors