



Mobile Man Anchor

The CE Approved Mobile Man Anchor has been specifically designed to provide short term safety for low frequency operations where guardrails are not provided. This portable anchor unit is ideal for short term maintenance operations to flat roofs or to the plant and equipment installed at roof level.



The Mobile Man Anchor is extremely compact, portable, easily assembled and features a unique design incorporating a shock absorber which reduces the total weight of the unit, making the product more "user friendly". The Mobile Man Anchor has been designed to be used with an approved shock absorbing rope grab and rope and full body harness to provide safe access at all times. The unit is fully galvanised to BS EN ISO 1461 : 1999 Hot Dip Galvanised Coatings, Specification and test methods. The anchor weights are supplied with fluted rubber, bonded to the underside. This protects the roof membrane and increases frictional resistance. The Mobile Man Anchor fully complies with BS EN 795: Protection against falls from a height - Anchor devices - Requirements and testing.

The Unit has also been designed to ensure compliance to the following Regulations:

- Work at Height Regulations 2005
- HS/G-33 Health & Safety in Roof work 1998
- Construction (Health, Safety & Welfare) Regulations 1996
- Construction (Design & Management) Regulations 1994
- Workplace (Health, Safety and Welfare) Regulations 1992
- Manual Handling Operations Regulations 1992

Total Protection (UK) Limited

142 Leyland Trading Estate Irthlingborough Road
Wellingborough Northamptonshire NN8 1RT

Tel: 0844 567 7423

info@totalprotectionuk.com

www.totalprotectionuk.com

Specialists in Safety: Working at Heights